《 COMMODITY DESCRIPTION 》

카탈로그 번호 Cat. No	품목번호 Item No	품목 및 규격 Description	단위 Unit	수량 Quantity
B04-02-150	LB-WD522	Digital Water Bath	set	1

A. Feature

1. 0.01 ℃ 온도 표시
2. 외부 센서 및 RS485 PC 통신용 포트 기본 장착
3. Seamless Stainless Steel Bath 사용
4. Bath 내부 용액을 편리하게 배출시킬 수 있는 Drain 장착 (LB-WD522)
5. PC cover를 사용하여 편리하게 내부를 관찰할 수 있음 (Option / LB-WD316제외)
6. Graphic LCD Display, 간편하고 직관적인 Controller 조작
7. Auto-Tuning 기능 및 온도 Calibration 기능
8. 2가지 타입의 타이머 (구동과 동시에 시작 & 목표 온도 도달 후 시작)
9. Automatical Fault Sensing System 기기 스스로 이상 상황을 감시 (특허)
10. 2중화 과온 안전장치, 1차 Controller 과온 Alarm과 2차 과온 차단 회로

B. Specifications

Model		LB-WD522
Capacity		22 L
Controller	Control	PID Control, Auto-tuning
	Display	GLCD (Graphic LCD)
	Resolution	0.01 ℃
	Timer	Run Start / Wait Start (99 hr 59 min)
Temperature	Range	Ambient +5 to +100 ℃
	Accuracy	±0.3 ℃ (at 50 ℃)
	Uniformity	±1.84 ℃ (at 50 ℃)
Dimension	Interior	w500 × d295 × h110 mm
	External	w535 × d330 × h260 mm
	Packing Dimension	w600 x d400 x h340 mm
Weight	Weight	10.2 kg
	Packing Weight	11.2 kg
Material	Interior	Stainless Steel 304
	External	Powder Coated Steel
Electric Supply	Power	1 Phase, 220 VAC, 50/60 Hz
	Max Consumption	2 kW (9.1 A)
	Power Line	Standard Plug
Other	Drain	1/4" Hose Nipple Male

Safety	Over Temp. Limiter & Current Protection, Automatical Fault Sensing System

C. Accessory

1. B04-01-085 / LI-USB / RS485 to USB Communication Cable (옵션)
2. B04-91-471 / ET101 / External Sensor (옵션)
3. H03-03-205 / SL-HSKIT / Support Kit (옵션)
4. B04-91-155 / LB-WDPL22 / Optional PC cover (옵션)

D. Remark

1. 사용자의 지정장소에 설치 후 1년 동안 무상보증.
2. PL Insurance (제조물배상책임보험)
3. Validation Service (IQ, OQ, PQ)
4. CE Mark
5. KC Mark

www.lklab.com LK LAB KOREA	㈜엘케이랩코리아	**TEL : 031-573-4952** **FAX : 031-571-4958**	**E-mail :** **info@lklab.com**